

INVERTERS				
230VAC/50Hz				
Sinewave				
		Dimensions hwxwd (mm)	Weight kg	Euro ex VAT
Phoenix 12/150	12V/180VA	72x132x200	2,7	116
Phoenix 12/220	12V/220VA	98x130x178	2,1	197
Phoenix 12/301	12V/350VA	72x155x237	3,5	189
Phoenix 12/300	12V/300VA	98x130x208	3,3	302
Phoenix 12/600	12V/600VA	107x187x227	6,5	473
Phoenix Inverter C 12/1200*	12V/1200VA	375x214x110	10	842
Phoenix Inverter C 12/1600*	12V/1600VA	375x214x110	10	1082
Phoenix Inverter 12/2500*	12V/2500VA	362x258x218	18	1575
Phoenix 24/150	24V/180VA	72x132x200	2,7	116
Phoenix 24/220	24V/220VA	98x130x178	2,1	197
Phoenix 24/301	24V/350VA	72x155x237	3,5	189
Phoenix 24/350	24V/350VA	98x130x208	3,3	312
Phoenix 24/800	24V/800VA	107x187x227	6,5	494
Phoenix Inverter C 24/1200*	24V/1200VA	375x214x110	10	842
Phoenix Inverter C 24/1600*	24V/1600VA	375x214x110	10	1082
Phoenix Inverter 24/3000*	24V/3000VA	362x258x218	18	1575
Phoenix 48/220	48V/220VA	73x110x210	2,1	257
Phoenix Inverter 48/800	48V/800VA	107x187x227	6,5	541
Phoenix Inverter C 48/1200*	48V/1200VA	375x214x110	10	1067
Phoenix Inverter C 48/1600*	48V/1600VA	375x214x110	10	1248
Phoenix Inverter 48/3000*	48V/3000VA	362x258x218	18	1846

INVERTER/CHARGERS				
230VAC/50Hz				
Sinewave				
		Dimensions hwxwd (mm)	Weight kg	Euro ex VAT
Phoenix Multi C 12/800/35*	12V/800VA/35A	375x214x110	10	760
Phoenix Multi C 12/1200/50*	12V/1200VA/50A	375x214x110	10	1034
Phoenix Multi C 12/1600/70*	12V/1600VA/70A	375x214x110	10	1368
Phoenix Multi C 24/800/16*	24V/800VA/16A	375x214x110	10	760
Phoenix Multi C 24/1200/25*	24V/1200VA/25A	375x214x110	10	1034
Phoenix Multi C 24/1600/40*	24V/1600VA/40A	375x214x110	10	1368
Phoenix Multi C 48/1200/12*	24V/1200VA/25A	375x214x110	10	1248
Phoenix Multi C 48/1600/20*	24V/1600VA/40A	375x214x110	10	1562
Phoenix Multi 48/3000/35*	48V/3000VA/35A	362x258x218	18	2291
Phoenix MultiPlus C 12/1200/50	12V/1200VA/50A	375x214x110	10	1156
Phoenix MultiPlus C 12/1600/70	12V/1600VA/70A	375x214x110	10	1490
Phoenix MultiPlus 12/2000/100*	12V/2000VA/100A	362x258x218	18	1781
Phoenix MultiPlus 12/2500/120*	12V/2500VA/120A	362x258x218	18	2082
Phoenix MultiPlus C 24/1200/25	24V/1200VA/25A	375x214x110	10	1156
Phoenix MultiPlus C 24/1600/40	24V/1600VA/40A	375x214x110	10	1490
Phoenix MultiPlus 24/2000/60*	24V/2000VA/60A	362x258x218	18	1781
Phoenix MultiPlus 24/3000/70*	24V/3000VA/70A	362x258x218	18	2082
Phoenix MultiPlus 48/3000/35*	48V/3000VA/35A	362x258x218	18	2718
30 A automatic AC transfer relay option in Multi 2500VA and 3000VA				667

BATTERY CHARGERS: waterproof				
230VAC/45-65Hz				
1 output				
		Dimensions hwxwd (mm)	Weight kg	Euro ex VAT
Blue Power 12/6 Waterproof (1)	12V/6A	36 x 80 x 155	0,85	187
Blue Power 12/15 Waterproof (1)	12V/15A	46 x 99 x 193	0,95	284
Blue Power 24/3 Waterproof (1)	24V/3A	36 x 80 x 155	0,85	187
Blue Power 24/8 Waterproof (1)	24V/8A	46 x 99 x 193	0,95	284

BATTERY CHARGERS: microprocessor controlled				
Universal input 90-265VAC/45-65Hz				
2x full current output + 1x 4A output				
		Dimensions hwxwd (mm)	Weight kg	Euro ex VAT
Phoenix Charger 12/30 (2+1)	12V/30A	350x200x108	3,8	410
Phoenix Charger 12/50 (2+1)	12V/50A	350x200x108	3,8	604
Phoenix Charger 24/16 (2+1)	24V/16A	350x200x108	3,8	417
Phoenix Charger 24/25 (2+1)	24V/25A	350x200x108	3,8	604

BATTERY CHARGERS: microprocessor controlled				
230VAC and 400VAC/45-65Hz				
1x full current output + 1x 4A output				
		Dimensions hwxwd (mm)	Weight kg	Euro ex VAT
Skylla-TG 24/30 (1+1)	24V/30A	365x250x147	5,5	779
Skylla-TG 24/50 (1+1)	24V/50A	365x250x147	5,5	926
Skylla-TG 24/80 (1+1)	24V/80A	365x250x257	10	1562
Skylla-TG 24/100 (1+1)	24V/100A	365x250x257	10	1832
Skylla-TG 24/100 3-phase (1+1)	24V/100A	515x260x265	23	2419
Skylla-TG 48/25 (1+1)	48V/25A	365x250x147	5,5	1299
Skylla-TG 48/50 (1+1)	48V/50A	365x250x257	10	2223

BATTERY CHARGERS: analog control					
Universal input 90-265VAC/45-65Hz					
3x full current output					
		Dimensions hwxwd (mm)	Weight kg	Euro ex VAT	
Centaur Charger 12/20 (3)	12V/20A	355x215x110	3,8	297	
Centaur Charger 12/30 (3)	12V/30A	355x215x110	3,8	377	
Centaur Charger 12/40 (3)	12V/40A	426x239x135	5	488	
Centaur Charger 12/50 (3)	12V/50A	426x239x135	5	552	
Centaur Charger 12/60 (3)	12V/60A	426x239x135	5	610	
Centaur Charger 12/80 (3)	12V/80A	505x255x130	12	899	
Centaur Charger 12/100 (3)	12V/16A	505x255x130	12	1219	
Centaur Charger 24/16 (3)	24V/16A	355x215x110	3,8	381	
Centaur Charger 24/30 (3)	24V/30A	426x239x135	5	533	
Centaur Charger 24/40 (3)	24V/40A	505x255x130	12	731	
Centaur Charger 24/60 (3)	24V/60A	505x255x130	12	838	
Centaur Charger 24/80 (3)	24V/80A	505x255x230	16	1217	
Centaur Charger 24/100 (3)	24V/100A	505x255x230	16	1509	

* VE.NET and VE.Bus enabled. Suitable for parallel, split phase and 3-phase operation

Battery Isolators					
		Dimensions hwxwd (mm)	Weight kg	Euro ex VAT	
Diode isolators					
Argo 702SC	2 batteries 70A	60x120x80	0,8	48	
Argo 903SC	3 batteries 90A	60x120x150	1,2	84	
Argo 1202SC	2 batteries 120A	60x120x100	1,2	84	
Argo 1203SC	3 batteries 120A	60x120x150	1,2	110	
Argo 1602SC	2 batteries 160A	60x120x150	1,2	110	
Argo 1603SC	3 batteries 160A	60x120x200	1,5	143	
FET Isolators					
Argo 1002-FET	2 batteries 100A	60x120x150	1,2	139	
Argo 1003-FET	3 batteries 100A	60x120x150	1,2	156	
Argo 2002-FET	2 batteries 200A	60x120x150	1,2	177	
Argo 2003-FET	3 batteries 200A	60x120x150	1,2	204	
Microprocessor controlled relay Isolators					
Cyrix 80/12	12V/80A	46 x 46 x 80	0,11	95	
Cyrix 80/24	24V/80A	46 x 46 x 80	0,11	95	
Cyrix 160/12	12V/160A	46 x 93 x 96	0,3	173	
Cyrix 160/24	24V/160A	46 x 93 x 96	0,3	173	
Cyrix 400/12	12V/400A	78 x 102 x 110	0,9	270	
Cyrix 400/24	24V/400A	78 x 102 x 110	0,9	270	

Battery Combining diodes					
		Dimensions hwxwd (mm)	Weight kg	Euro ex VAT	
BCD 302	2 batteries 30A	60x120x80	0,6	59	
BCD 702	2 batteries 70A	60x120x80	0,8	82	
BCD 703	3 batteries 70A	60x120x100	0,8	126	

Battery disconnect switch					
		Dimensions hwxwd (mm)	Weight kg	Euro ex VAT	
BatteryProtect BP-25	25A	49x88x68	0,2	84	
BatteryProtect BP-60	60A	80x60x40	0,2	126	

Battery Monitor					
		Dimensions hwxwd (mm)	Weight kg	Euro ex VAT	
Battery monitor BMV-501		65x65x72	0,3	316	
BMV-501 Prescaler 5:1				95	
BMV-501 Connection kit 10m				63	
BMV-501 Connection kit 15m				78	
BMV-501 Connection kit 20m				99	
BMV-501 Connection kit 30m				133	
BMV-501 Temp.sensor kit 10m				36	
BMV-501 Temp.sensor kit 20m				57	
BMV-501 Temp.sensor kit 30m				76	
BMV-501 Data Link RS232				219	

DC distribution kit					
		Dimensions hwxwd (mm)	Weight kg	Euro ex VAT	
On mounting plate		280x340x120	3	476	
With enclosure		300x380x210	5	640	

* VE.NET and VE.Bus enabled. Suitable for parallel, split phase and 3-phase operation

Prices can vary, dependent on local conditions.

All prices are per unit.
All prices are exclusive of VAT and other taxes.
Prices include Delivery in the Netherlands

Warranty to end users: 24 months from date of purchase

All our quotations, sales, deliveries and services are subject to our General Conditions of Delivery and Sale

DC/DC Converters		Dimensions hxwx d (mm)	Weight kg	Euro ex VAT
Not isolated				
Orion 24/12-5	18-35V/13,2V-5A	49x88x68	0,17	46
Orion 24/12-8	18-35V/13,2V-8A	49x88x98	0,25	57
Orion 24/12-12	20-35V/13,2V-12A	49x88x98	0,26	63
Orion 24/12-20	20-35V/13,8V-20A	49x88x126	0,48	86
Orion 24/12-30	20-35V/13,8V-30A	49x88x151	0,6	126
Orion 24/12-60	20-35V/13,8V-60A	88x100x180	1,2	293
Orion 12/24-7	9-18V/24V-7A	49x88x98	0,3	86
Orion 12/24-10	9-18V/24V-10A	49x88x12	0,4	110
With galvanic isolation (xx=input=12, 24, 48, or 96 VDC yy=output=12 or 24VDC)				
Orion xx/yy-100W		49 x 88 x 152	0,5	112
Orion xx/yy-200W		49 x 88 x 182	0,6	133
Orion xx/yy-360W		64 x 163 x 160	1,4	270
Orion 12/27,6-12	9-18V/27,6-12A	64 x 163 x 160	1,4	295
Orion 7-35/12-3	7-35V/12,6V-3A	64 x 163 x 160	1,4	88

Order and Handlingcosts € 15 per order
Prices include Delivery in the Netherlands

Delivery when stockitem usual within 3 workingdays

Isolation Transformer		Dimensions hxwx d (mm)	Weight kg	Euro ex VAT
Isolation Transformer 1800W	115/230V 16/8A	375x214x110	10	362
Isolation Transformer 3600W	230V/16A	362x258x218	23	537
Isolation Transformer 3600W	115/230V 30/16A	362x258x218	23	665
Isolation Transformer 7000W	230V/30A	362x258x218	24	724

Automatic Transfer Switches		Dimensions hxwx d (mm)	Weight kg	Euro ex VAT
Filax	230V/3,5kW	200x120x75	0,8	381
PowerMan 230/25-0	230V/25A	200x300x120	7	815
PowerMan 230/50-0	230V/50A	200x300x120	8	1088
PowerMan 230/80-0	230V/80A	300x380x210	9	1438
PowerMan 230/40-1	230V/40A	300x380x210	11	1156
PowerMan 230/80-1	230V/80A	500x500x210	22	1429
PowerMan 230/40-2	230V/40A	600x380x210	22	1701
PowerMan 230/80-2	230V/80A	600x600x210	30	2246

Remote Panels		Dimensions hxwx d (mm)	Euro ex VAT
Battery Alarm		65x120x40	76
Phoenix Multi Control 16A		65x120x40	110
Phoenix Multi Control 30A		65x120x40	145
Phoenix PowerMan Control 16A		65x120x40	217
Phoenix PowerMan Control 30A		65x120x40	217
Phoenix Inverter Control		65x60x40	76
Phoenix Charger Control		65x120x40	76
AC Outlet		65x60x40	59
Auxiliary		65x60x40	53
Charger Output		65x60x40	59
Charger Switch		65x60x40	72
Temperature Sensor (old products)		65x60x40	61
Skylla Control		65x60x40	118

Connection Cables and interface		Euro ex VAT
UTP Patch lead 5 m		19
UTP Patch lead 10 m		23
UTP Patch lead 15 m		27
UTP Patch lead 30 m		34
Flatcable for parallel connect		29
Connection bag 3-phase operation		177
Victron Interface MK.1b		57
RS232 to USB converter		30

